
GRASS TIOMOS 110° SOFT CLOSE HINGES



Tiomos Night - anthracite finish

Nickel-plated finish

Drilling pattern for cup fixing




Drilling pattern for screw fixing



Dowel/Impresso tool free fixing



Impresso tool free fixing also suits above




> For standard applications

- > Opening angle 110° (can be restricted to 85°, see page 73 for details), Ø 35 mm cup
- > For door thickness up to 24 mm (for door thicknesses 24 mm and above, a trial fitting is recommended)
- > Up to 24 mm overlay using full overlay plus hinge (see page 43)
- > Available with or without integrated soft close
- > Screw fixing, dowel or impresso (quick fix) fixing cup
- > Click on arm
- Full overlay and full overlay plus mounting has steel cup and hinge arm. Half overlay and inset mounting has steel cup and zinc alloy arm
- > Tiomos Night, anthracite finish, also available
- > Order fixing screws separately
- > Order qty: 1 pc

Minimum gap for doors with chamfered edges (r = 1 mm) with factory setting

Door thickness	Distance to cup E mm					
mm	3.0	4.0	5.0	6.0	7.0	
16	0.6	0.6	0.6	0.6	0.6	
17	0.6	0.6	0.6	0.6	0.6	
18	0.7	0.7	0.7	0.7	0.7	
19	0.9	0.9	0.9	0.9	0.9	
20	1.1	1.1	1.1	1.1	1.1	
21	1.4	1.3	1.3	1.3	1.3	
22	1.6	1.6	1.6	1.5	1.5	
24	2.4	2.1	2.1	2.1	2.0	
	Minim	Minimum gap F				

Grass Tiomos 110° concealed hinge, full overlay mounting



Application example with 2 mm mounting plate shown - see table opposite for details

Door ove	erlay mm						
13	14	15	16	17	18	19	
		3	4	5	6	7	0
3	4	5	6	7			2
Distance to cup E mm			Мо	untina p	late heid	aht mm	







TCH TECHNOLOGY 2018, © Häfele U.K. Ltd 2016.


Soft close	Screw fixing	Impresso	Dowel		
Nickel-plated	l finish				
With	348.31.801	348.31.831	348.31.811		
Without	348.31.601	348.31.631	-		
Tiomos Night - anthracite finish					
With	348.31.805	-	-		



Most of the products you will find in this Directory are available within 24 hours. However, to be able to offer the breadth of range in our collection, a small number of products have a longer lead time that is typically around 14 days. Please call 0800 171 2909 for an accurate delivery date when you see this symbol.

HAFELE

Grass Tiomos 110° concealed hinge, half overlay/twin mounting



Application example with 2 mm mounting plate shown - see table opposite for details

Door ove	erlay mm						
6.5	7.5	8.5	9.5	10.5	11.5	12.5	
		3	4	5	6	7	0
3	4	5	6	7			2
Distance to cup F mm			Moi	ıntina nl	ate heid	nht mm	




GRASS
25
YEAR WARRANTY



Soft close	Finish	Screw fixing	Impresso		
With	Nickel-plated	348.31.802	348.31.832		
Without	Nickel-plated	348.31.602	-		
Tiomos Night					
With	Anthracite	348.31.806	⊘ -		

Grass Tiomos 110° concealed hinge, inset mounting



Application example with 2 mm mounting plate shown - see table opposite for details

Door gap mm					
4	3	2	1	0	
			3	4	0
	3	4	5	6	2
Distance to cup E mm		Mou	nting pla	ate heig	ht mm








Soft close	Finish	Screw fixing	Impresso				
With	Nickel-plated	348.31.803	348.31.833				
Without	Nickel-plated	348.31.603	-				
Tiomos Ni	Tiomos Night						
With	Anthracite	348.31.807	-				

Grass Tiomos 110° concealed hinge, full overlay plus



reserve the right to alter specifications without notice

TCH TECHNOLOGY 2018, © Häfele U.K. Ltd 2016. Dimensional data not binding. We

Application example with 2 mm mounting plate shown - see table opposite for details

Door ove	rlay mm						
16	17	18	19	20	21	22*	
		3	4	5	6	7	0
3	4	5	6	7			2
Distance to cup E mm			Мо	unting p	late heiç	ght mm	

*door overlay from 24 mm, use mounting plate 348.38.560 on page 68







Soft close	Finish	Screw fixing	Impresso	
With	Nickel-plated	348.31.800	348.31.830	
Without	Nickel-plated	348.31.600	-	

YOU ALSO NEED:






OPTIONAL ACCESSORIES
Pages 73-74, 109-121

Grass Tiomos cruciform mounting plate, 4 point fixing






- > For TIOMOS click on fixing hinges only
- > Hospa screw fixing
- > Two part plate with ± 2 mm height adjustment via worm screw
- > Nickel-plated steel
- > Order fixing screws separately
- > Order qty: 1 pc







A wider range of mounting plates are shown on pages **66-68**



TIOMOS CLICK ON MOUNTING PLATES AND ACCESSORIES




TIOMOS click on fixing hinges are shown on pages 36-63

Grass Tiomos cruciform mounting plate, 4 point fixing



Nickel-plated



For Hospa screws

- > For TIOMOS click on fixing hinges only
- > Hospa screw fixing or with pre-mounted Euro screws or dowel fixing
- > Two part plate with ± 2 mm height adjustment via worm screw
- > Order fixing screws separately for Hospa screw fixing versions
- > Order qty: 1 pc



Nickel-plated




Anthracite







Nickel-plated



With dowel fixing







Height	Hospa screw	Pre-mounted	Dowel				
Nickel-plated fi	nish						
0 mm	348.38.511	348.38.521	348.38.541				
2 mm	348.38.512	348.38.522	348.38.542				
3 mm	348.38.513	348.38.523	-				
Tiomos Night	Tiomos Night - Anthracite finish						
0 mm	348.38.040	348.38.050	-				
2 mm	348.38.042	348.38.052	-				

Grass Tiomos inline mounting plate




Nickel-plated

Anthracite





For Varianta



- > Varianta screw fixing or dowel fixing
- > Two part plate with \pm 2 mm height adjustment via worm screw
- > Order fixing screws separately for Varianta screw fixing versions
- > Order qty: 1 pc






data not binding. We


TCH TECHNOLOGY 2018, © Häfele U.K. Ltd 2018. Dimensional



Nickel-plated







_	_
	-

Order Varianta screw 013.01.711 separately for screw fixing version to ensure correct fit, shown in Section 13 on page 22

Height	Screw fixing	Dowel
Nickel-plated finish		
0 mm	348.38.501	348.38.010
2 mm	348.38.502	348.38.012
3 mm	348.38.503	-
Tiomos Night - Anthracite finis	sh	
0 mm	348.38.030	-
2 mm	348.38.032	-
3 mm	348.38.033	⊘ -




Most of the products you will find in this catalogue are available within 24 hours. However, to be able to offer the breadth of range in our collection, a small number of products have a longer lead time that is typically around 14 days. Please call 0800 171 2909 for an accurate delivery date when you see this symbol.

HAFELE

Grass Tiomos cruciform mounting plates, 2 point fixing





- > For TIOMOS click on fixing hinges only
- > Hospa screw fixing
- ightharpoonup Two part plate with \pm 2 mm height adjustment via worm screw
- > Nickel-plated steel
- > Order fixing screws separately
- > Order qty: 1 pc







Height	Hospa screw
6 mm	348.39.511
8 mm	348.39.512
14 mm	348.39.536
19 mm	348.39.519
21 mm	348.39.520


Grass Tiomos inset beaded mounting plate for frame constructions, 3 point fixing



- > For inset doors
- > To be used with TIOMOS half overlay hinges
- > Hospa screw fixing
- > With convenient height adjustment ±2 mm via worm screw
- > Nickel-plated steel and zinc alloy
- > Order fixing screws separately
- > Order qty: 1 pc







Door thickne	ess mr	n							
	16	18	19	20	22	24	26	28	
	3	3	3	3	3	3	3	3	4
	4	4	4	4	4	4	4		3
	5	5	5	5	5	5			2
	6	6	6	6					1
Distance to	cup m	m			Mi	nimur	n reve	eal mm)






0 mm 348.38.020	Height	Cat. No.
	0 mm	348.38.020


Grass Tiomos ECON cruciform mounting plate, 3 point fixing





For Hospa screws






With pre-mounted Euro screws

- > For TIOMOS click on fixing hinges only
- > Hospa screw fixing or with pre-mounted Euro screws or dowel fixing
- \gt One part plate with \pm 2.5 mm height adjustment by slot
- > Nickel-plated steel
- > Order fixing screws separately for Hospa screw fixing versions
- > Order qty: 1 pc





With dowel fixing



TIOMOS click on fixing hinges are shown on pages **36-63**







Height	Hospa screw	Pre-mounted	Dowel	
0 mm	348.38.612	348.38.551	348.38.591	
2 mm	348.38.613	348.38.552	348.38.592	
-2 mm	348.38.560	-	-	

Cover caps





> Steel

> Order qty: 1 pc



Suitable for	Hinge arm	Hinge cup	
Nickel-plated finish	348.40.000	348.40.001	
Night - Anthracite finish	348.40.005	348.40.006	

Grass Tiomos cover caps, with Grass logo



- > Suitable for hinge arm
- > With GRASS logo embossed
- > Nickel-plated steel
- > Order qty: 1 pc




Hand	Right	Left	
Cat. No.	348.40.003	348.40.004	

Grass Tiomos wedge



Wedge +5°

Wedge -5°



> Ideal for curved door applications

- > For cruciform mounting plates that require underlaying either +/- 5°
- > For screwing into 32/37 mm series drilled holes
- > Nickel plated zinc alloy
- > *Max. 3 wedges stacked on top of each other
- > Order qty: 1 pc



TCH TECHNOLOGY 2018, © Häfele U.K. Ltd 2018. Dime

	Cat. No.
Wedge + 5° *	348.40.020
Wedge - 5°	348.40.021

