

7

# IXCONNECT RED JIG SUPPLEMENTARY PARTS

Supplementary parts for red jig basic jig and supplementary jigs shown on pages 42-43B.

## Red jig supplementary parts



- A Red jig drill guides for connectors and series drilled holes
  - B Depth gauges, supplied with 1x depth gauge, stop ring, spiral spring
  - C Marking pin Ø 3/5 mm
  - D Stop rings for HS twist drill bit Ø 8 mm or Ø 10 mm
  - E Inserts for 5, 8, 10 or 11 mm
  - F Marking gauge
  - G Stop plate with 2 special screws
  - H Twist drill bit for wood, HM, total length 130 mm, shank Ø 8 mm (depth gauge 15)
  - I Multi-spur drill bits, HM, total length 130 mm, shank Ø 10 mm (depth gauge 32 and 48)
  - J Multi-spur drill bits, HM/HW, 3-spur, total length 130 mm, shank Ø 10 mm (depth gauge 32 and 48)  
Ø 20 mm version with countersinker for wood thickness 19 mm
  - K Twist drill bits for wood, HS, total length 110 mm
  - L Universal bit holder with quick release chuck, length 60 mm, 1/4" chuck, 1/4" drive, with permanent magnet
- > Order qty: 1 pc



| Item   | Cat. No.   |
|--|------------|
| A Guide for Minifix 12/15                        | 001.25.660 |
| Guide for Maxifix, tightening distances 55/35 mm | 001.25.643 |
| Guide for Rafix 20, Tab 18, OneFix               | 001.25.625 |
| Guide for hole systems at 37/69 mm intervals     | 001.25.620 |
| Guide for Ø 35 concealed hinges, 48/6 pattern    | 001.25.731 |
| Guide for Ø 35 concealed hinges, 45/9.5 pattern  | 001.25.732 |
| B Depth gauge 15 mm, up to drill bit Ø 3-10 mm   | 001.25.770 |
| Depth gauge 132 mm, up to drill bit Ø 12-25 mm   | 001.25.771 |
| Depth gauge 148 mm, up to drill bit Ø 26-40 mm   | 001.25.772 |
| C Marking pin Ø 3/5 mm                           | 001.25.766 |
| D Stop ring for HS twist drill bit Ø 8 mm        | 001.42.683 |
| Stop ring for HS twist drill bit Ø 10 mm         | 001.42.693 |
| E Insert 5 mm                                    | 001.25.763 |
| Insert 8 mm                                      | 001.25.760 |
| Insert 10 mm                                     | 001.25.761 |
| Insert 11 mm                                     | 001.25.762 |
| F Marking gauge                                  | 001.27.060 |
| G Stop plate with 2 special screws               | 001.25.063 |
| H Twist drill bit Ø 3 mm                         | 001.06.682 |
| Twist drill bit Ø 5 mm                           | 001.06.683 |
| Twist drill bit Ø 8 mm                           | 001.06.686 |
| Twist drill bit Ø 10 mm                          | 001.06.687 |
| I Multi-spur drill bit, HM, Ø 12 mm              | 001.06.661 |
| Multi-spur drill bit, HM, Ø 15 mm                | 001.06.662 |
| Multi-spur drill bit, HM, Ø 35 mm                | 001.06.669 |
| J Multi-spur drill bit, HM/HW, Ø 18 mm           | 001.24.454 |
| Multi-spur drill bit, HM/HW, Ø 20 mm             | 001.24.417 |
| K Twist drill bit, Ø 8 mm                        | 001.20.508 |
| Twist drill bit, Ø 10 mm                         | 001.20.510 |
| L Bit holder                                     | 006.37.250 |



Red jig basic jig and supplementary jigs are shown on pages 42-43B