



# HÄFELE METALLA A 110° STRAIGHT SLIDE HINGES



- > Full overlay mounting
- > Without soft close
- > Opening angle 110°, Ø 35 mm cup
- > Screw fixing cup
- > Drilling depth hinge cup: 12 mm
- > Slide on arm
- > For 14-26 mm door thickness
- > Side adjustment 3 mm, height adjustment 2 mm (via mounting plate), depth adjustment 2 mm
- > Steel cup and hinge arm, nickel-plated
- > Order fixing screws separately
- > Order qty: Multiples of 250 pcs



**Metalla A concealed hinge, straight slide, 48/6.0, full overlay, 110°**



Overlay - coverage of the side end by door e mm								
10	11	12	13	14	15	16	17	18
				3	4	5	6	7
		3	4	5	6	7		
3	4	5	6	7				

DBE distance to cup bore edge mm      Mounting plate height f mm

Note: The values (distance to cup) in the table apply to centre position of side adjusting screw



Fixing	Slide on
Screw fixing	311.88.530

**Slide on mounting plate for Metalla A concealed hinge, combi cruciform**



- > Hospa screw fixing or pre-mounted with euro screw
- > One part plate with ± 2 mm height adjustment via slot
- > Nickel-plated steel
- > Order fixing screws separately for Hospa screw fixing versions
- > Order qty: 1 pc



Height	Hospa screws	Euro screws
0 mm	311.03.101	311.03.108
4 mm	311.03.103	-

TCH TECHNOLOGY 2018, © Häfele U.K. Ltd 2018. Dimensional data not binding. We reserve the right to alter specifications without notice.