
9

Furniture Hinges and Flap Fittings: Hinges

# GRASS NEXIS 170° HINGES






- Zero protrusion makes this hinge ideal for cabinets with internal drawer boxes or pull out shelves
- > Opening angle 170° (Can be reduced to 120°, see page 104)
- > Sprung
- > Ø 35 mm cup
- > Screw fixing
- > Choice of slide on or click on arms
- > Soft close compatible
- > With finger protection
- > Heavy duty, for doors up to 26 mm thick see table below
- > For doors more than 23.5 mm please try test installation first
- > Nickel-plated zinc alloy cup and arm
- > Order fixing screws separately for screw fixing versions
- > Order qty: 1 pc


#### 170° Hinge


Door thickness	Distance to cup E mm					
mm	3.0	4.0	5.0	6.0	7.0	
16	0.0	0.0	0.0	0.0	0.0	
18	0.0	0.0	0.0	0.0	0.0	
19	0.0	0.0	0.0	0.0	0.0	
20	0.0	0.0	0.0	0.0	0.0	
22	0.0	0.0	0.0	0.0	0.0	
23	0.0	0.0	0.0	0.0	0.0	
24	0.0	0.0	0.0	0.5	1.8	
25	6.5	6.5	6.0	5.5	4.8	
26	10.5	9.5	8.5	7.5	6.5	
	Minim	um gap				

Zero protrusion for application with inset drawers. With 0 cranking and 0 height of mounting plate the door is flush with the cabinet at 90°



## Grass Nexis 170° concealed hinge, full overlay/inset mounting





With full overlay mounting, cup distance 3mm and mounting plate height 18 mm an inset application is achieved.

Door ove	erlay mm						
15	16	17	18	19	20	21	
		4	5	6	7	8	0
4	5	6	7	8			2
Distance	Distance to cup E mm			Mou	unting pla	ate dist	ance mm

170°		GRASS 255 YEAR WARRANTY WARRANTY
Fixing	Slide on	Click on
Screw fixing	323.21.609	322.21.630




18 mm mounting plate for inset mounting shown on page **100** 



PAGE AMENDED 21.08.18/1



#### Grass Nexis 170° concealed hinge, half overlay/twin mounting



Mounting plate height 2 mm

Door ove	rlay mm						
6	7	8	9	10	11	12	
			4	5	6	7	0
	4	5	6	7	8		2
Distance	to cup I	Emm		Mol	unting pla	ate dista	ance mm

SORIES

9

FIXING S		
Screw fixing	323.21.618	322.21.631
Fixing	Slide on	Click on
		WARRAN

Grass Nexis super compact cruciform mounting plate



YOU ALSO NEED:



MOUNTING PLATES

Pages 100-102



> For Hospa screw fixing

- > Two part plate with external height adjustment
- > Nickel-plated zinc alloy and pressed steel
- > Order fixing screws separately > Order qty: 1 pc

Height

0 mm

2 mm

Slide on

323.85.701

323.85.729

	(	_	1

Click on

A wider range of mounting plates are shown on pages 100-102

Slide on

Grass Nexis soft close fitting, for screw fixing cup



Max. 2500 mm

Max. 2200 mm Max 600 mm

> Max. 900 mm

Ο



600 mm 16-22 kg 🔘

0

10-15 kg

C

0 0 0

1 1 2 2

Recommended position for Soft close

6-9 kg

4-5 kg

- > For use with sprung 170° concealed hinges with screw or dowel fixing cup
- > The quantity and position of soft close will depend on door height and weight, see chart left

Click on

322.85.750

322.85.752

- > No fixing materials required, clips onto hinge arm
- > Zinc alloy
- > Order qty: 1 pc

Finish




# MOUNTING PLATES FOR NEXIS CLICK ON HINGES



Nexis click on hinges are shown on pages 72-89

## Grass Nexis super compact cruciform mounting plate



For Varianta screws





- > For click on systems
- > Varianta or Hospa screw fixing
- > Two part plate with external height adjustment
- > Nickel-plated zinc alloy and pressed steel > Order fixing screws separately
- > Order qty: 1 pc

FIXINGS REQUIRED




	⇔5	Ø 3.5	RANTY
Height	Varianta screws	Hospa screw	
0 mm	322.86.750	322.85.750	
2 mm	322.86.752	322.85.752	
4 mm	322.86.754	322.85.754	
8 mm	322.86.758	322.85.758	
18 mm	322.86.759	322.85.759	
-			

Information on mounting plate adjustment is shown on page 33


### Grass Nexis cruciform mounting plate





With pre-mounted Euro screws





> For click on systems
------------------------

- > With pre mounted euro screws or Hospa screw fixing
- > One part plate with external height adjustment
- > Nickel-plated pressed steel
- > Order fixing screws separately for Hospa screw fixing versions
- > Order qty: 1 pc

		HOSPA Ø 3.5	YEAR WARRANT
Height	Pre-mounted Euro screws	Hospa screw	
0 mm	322.94.710	322.94.700	
2 mm	322.94.712	322.94.702	
4 mm	322.94.714	322.94.704	

Fixings

PAGE AMENDED 13.04.18/1



### Grass Nexis cruciform cam adjusting mounting plate





With pre-mounted Euro screws



TCH TECHNOLOGY 2018, @ Häfele U.K. Ltd 2018. Dimensional data not binding. We reserve the right to alter specifications without notice.



For Hospa screws

- > For click on systems
- > With pre-mounted Euro screws or Hospa screw fixing
- > Two part plate, eccentric cam adjusting
- Nickel-plated zinc alloy
- > Order fixing screws separately for Hospa screw fixing versions
- > Order qty: 1 pc


25

9

Fixings included	FIXINGS REQUIRED HOSPA Ø 3.5
e-mounted Euro screws	Hospa screw
322.89.720	322.89.700

Height	Pre-mounted Euro screws	Hospa screw	
0 mm	322.89.720	322.89.700	
2 mm	322.89.722	322.89.702	
4 mm	-	322.89.704	
8 mm	-	322.89.708	
-			

### Grass Nexis straight cam adjusting mounting plate



#### > For click on systems

- > Hospa screw fixing
- > Two part plate, eccentric cam adjusting
- > Nickel-plated zinc alloy
- > Order fixing screws separately
- > Order qty: 1 pc

Height	Hospa screw
0 mm	322.72.720
2 mm	322.72.722
4 mm	322.72.724





# GRASS MOUNTING PLATES FOR NEXIS SLIDE ON HINGES



Nexis slide on hinges are shown on pages 72-89

Grass Nexis super compact cruciform mounting plate





32



> For slide on systems > Varianta or Hospa screw fixing

- > Two part plate with external height adjustment
- > Nickel-plated zinc alloy and pressed steel
- > Order fixing screws separately
- > Order qty: 1 pc

	FIXINGS REQUIRED VARIANIA ©5	FIXINGS REQUIRED HOSPA Ø 3.5
Height	Varianta screws	Hospa screw
0 mm	323.86.708	323.85.701
2 mm	-	323.85.729
4 mm	323.86.744	323.85.747



Furniture Hinges and Flap Fittings: Hinges


9

Information on mounting plate adjustment is shown on page 33

### Grass Nexis super compact cruciform mounting plate









## Grass Nexis straight mounting plate





- > For slide on systems
- > With Pre-mounted Euro screws or Hospa screw fixing
- > One part plate with external height adjustment
- > Nickel-plated pressed steel
- > Order fixing screws separately for Hospa screw fixing versions
- > Order qty: 1 pc

	Fixings included	FEXINGS REQUIRED HOSPA Ø 3.5
Height	Pre-mounted Euro screws	Hospa screw
0 mm	323.84.704	323.83.707
2 mm	323.84.722	323.83.725
4 mm	323.84.740	323.83.743

- > For slide on systems
- > Hospa screw fixing
- > Two part plate with internal height adjustment
- > Nickel-plated zinc alloy and pressed steel
- > Order fixing screws separately
- > Order qty: 1 pc

	Ø 4.0
Height	Hospa screw
0 mm	323.71.707
2 mm	323.71.725
4 mm	323.71.743





9

Furniture Hinges and Flap Fittings: Hinges

grass **25** 

## GRASS COVER PLATES FOR NEXIS HINGES



Nexis slide on hinges are shown on pages **72-89** 

### Grass hinge cup cover cap

	<ul> <li>For use with Ø 35 mm cup hinges s</li> <li>Covers screw fixing hinge cup of the aesthetic appearance</li> <li>No fixing materials required, clips or</li> <li>Zinc alloy</li> <li>Order qty: 1 pc</li> </ul>	ose hinges without soft close for
	Finish	Cat. No.
	Nickel-plated	322.67.191
Grass hinge arm cover plate		
	<ul> <li>&gt; Please note: Cover plate to match compatible</li> <li>&gt; Nickel-plated steel</li> <li>&gt; Order qty: 1 pc</li> </ul>	full overlay hinge is not soft close

		WARRANT
To match	Full overlay	Half overlay
Cat. No.	323.68.300	323.68.310

#### ACCESSORIES AND INSTALLATION 600 mm 16-22 kg TOOLS FOR NEXIS HINGES 10-15 kg 🔘 Max. 2500 mm 6-9 ka Max. 2200 mn Max 1600 mm 4-5 ka C Max 900 mm 0 0 0 Nexis hinges are shown on pages 72-89 1 1 2 2 Ο Recommended position for Soft close Grass soft close fitting, for screw fixing cup > For use with 95°/100°/110°/125°/45°/30°/post/-24°/-14° sprung concealed hinges with screw fixing cup > The quantity and position of soft close will depend on door height and weight, see chart above > No fixing materials required, clips onto hinge cup > Zinc alloy > Order qty: 1 pc Finish Cat. No. Nickel-plated 322.67.190 Grass soft close fitting, for screw fixing cup > For use with sprung 170° concealed hinges with screw or dowel fixing cup - shown on page 78-79 > The quantity and position of soft close will depend on door height and weight, see chart above > No fixing materials required, clips onto hinge arm > Zinc alloy > Order qty: 1 pc Cat. No. Finish Nickel-plated 322.67.170 Grass opening angle reduction clip for 170° hinge > For use with sprung 170° concealed hinges - shown on page 78-79 > Reduces the opening angle to 120° > Prevents doors from coliding with the cabinet side in inset or mitred corner applications > Black plastic > Order qty: 1 pc Cat. No. For use with 170° hinge 322.66.320 Grass opening angle reduction clip for 110° hinge > Reduces the opening angle to 85° > Prevents doors from coliding with fronts or walls in corner applications > For use with 110° hinges shown on page 76 > Black plastic > Order qty: 1 pc Cat. No. 322.66.310 For use with 110° hinge

Furniture Hinges and Flap Fittings: Hinges

9

Section 9 104



#### Grass jig for mounting plates and hinges



#### > For use with all Click on hinges and mounting plates

> For drilling holes for hinges with either screw fixing or pre-mounted

- > For overlay installation only
- > Reversible
- Black plastic
- > Order qty: 1 pc

Mounting plate jig

euro screws

> 2x drill Ø 8 mm
> 1x drill Ø 35 mm
> Bit for boring machine
> Order qty: 1 pc

> Bit for hand drill machine

> With template for wing mounting plate

Cat. No. 001.33.160

Grass drilling jig 500













	YEAF WARRA
Drilling pattern	Cat. No.
48/9	001.33.400

> Available to order separately

> Order qty: 1 pc

Grass mounting plate jig



	GRJ 2 VE WARR
	Cat. No.
Mounting plate jig	001.33.420

Furniture Hinges and Flap Fittings: Hinges



