

LOOX 12V LED 2090 DOWNLIGHT, MODULAR, Ø 32.5 MM

Modular downlight - order from choice of four bezel designs for surface mounting, or recess mount in Ø 26 mm hole. Downlight includes Samsung LEDs and has a narrow beam angle for staging objects.

5

Lighting: Loox LED




Loox 12V LED 2090 downlight, Ø 32.5 mm



Modular design -

Round or square, surface or recess mounting bezels. 2.0 m lead with snap-in connector included.



- > Equipped with high quality Samsung LEDs
- > With narrow beam angle for staging objects
- > 1.7 mm rim, min. 11 mm hole depth required
- > For recess mounting, press-fit in Ø 26 mm hole, order bezel separately
- > For surface mounting, order bezel separately
- > Voltage: 12V. Wattage: 1.2W
- > Dimmable
- > Degree of protection:
 - IP44 as recess mounted downlight
 - IP20 as surface mounted downlight
- > With 2.0 m lead with Loox 12V connector
- > Silver coloured aluminium housing
- > Order qty: 1 pc

Distance	55°	2700 K	3000 K	4000 K	5000 K
250 mm		930 Lx	990 Lx	1005 Lx	1005 Lx
500 mm		230 Lx	240 Lx	250 Lx	260 Lx
750 mm		95 Lx	100 Lx	110 Lx	115 Lx
1000 mm		50 Lx	55 Lx	60 Lx	60 Lx

Output:	2700 K	3000 K	4000 K	5000 K
Light colour:	Warm white	Warm white	Cool white	Cool white
Wattage (W):	1.2	1.2	1.2	1.2
Energy efficiency:	A+	A+	A+	A+
Number of diodes:	1	1	1	1
Light output (Lm):	80	90	95	100
Efficacy (Lm/W):	67	75	79	83
CRI Ra/R9:	>90/>60	>90/>60	>90/>60	>90/>60



For recess or surface mounting order bezel separately, shown on page 5.27

12V

Output	2700 k	3000 K	4000 K	5000 K
Cat. No.	833.70.280	833.70.281	833.70.282	833.70.283

YOU ALSO NEED:

DRIVER
Page 105

SWITCH
Pages 107-110

OPTIONAL ACCESSORIES
Pages 106, 112-114