EXTRA

NARROW

5 mm

HXFELE

LOOX5 12V LED 2060 FLEXIBLE STRIP LIGHT MONOCHROME, 5 MM

Loox5 lights are high performance offering more output and can also be remote controlled using the Häfele Connect Mesh system. The LED 2060 strip light is the narrowest strip at just 5 mm wide and has 120 high quality Samsung LEDs per metre, available in either 5 or 15 m lengths. Ideal for ambient lighting and is easy to retrofit due to self adhesive fixing. Can be shortened every 25 mm.



Aluminium profiles are available to order separately, shown from page 5.184



Loox5 12V LED 2060 flexible strip light, 4.8W/m, 5 mm width




- X ¥₩ 5.5_
- Cut LED strip light to length (one contact side remains on the remainder piece; reusable)
- Connect LED strip lights (two contact sides required)

C = section length: 25 mm

P = length of contact surface: 3.0 mm

- > Equipped with high quality Samsung LEDs
- > For surface mounting, self adhesive, 5 or 15 m length
- > Can be shortened every 25 mm
- > Voltage: 12V. Wattage: 24 or 72W (4.8W per metre)
- > Dimmable
- > Degree of protection: IP20
- > Lifetime: >50,000 h
- > Width: 5 mm
- > Height: 1.3 mm
- > Lead not included, must be ordered separately
- > White plastic
- > Order qty: 1 pc (roll of 5 or 15 m length)

Distance	120°	2700 K	3000 K	4000 K	5000 K
250 mm		940 Lx	970 Lx	1000 Lx	1030 Lx
500 mm		400 Lx	420 Lx	430 Lx	430 Lx
750 mm		220 Lx	235 Lx	240 Lx	240 Lx
1000 mm		135 Lx	145 Lx	145 Lx	145 Lx
The values apply to a strip light length of 1 m					





- > Maximum strip length is dependant on driver wattage capacity, shown on page 5.156
- > Maximum recommended strip light length for optimum visual light output: 4.0 m
- > Lead must be ordered separately, shown on page **5.170**

Output:	2700 K	3000 K	4000 K	5000 K
Light colour:	Warm white		Cool	white
Wattage (W):	4.8W per meter			
Energy efficiency:	A+	A+	A+	A+
Number of diodes:	120 per meter			
Light output (Lm/m):	440	460	480	495
Efficacy (Lm/W):	92	96	100	103
CRI Ra / R9:	>90 / >50			













Length	2700 K	3000 K	4000 K	5000 K
5 m	833.74.320	833.74.321	833.74.322	833.74.323
15 m	833.74.324	833.74.325	833.74.326	833.74.327

YOU ALSO NEED:







OPTIONAL ACCESSORIES Pages 5.158-159, 5.167-168, 5.178-181