## HXFELE

## LOOX5 24V LED 3042 FLEXIBLE STRIP LIGHT, MONOCHROME, 8 MM

Loox5 lights are high performance offering more output and can also be remote controlled using the Häfele Connect Mesh system. The 5 m LED 3042 strip light with 600 high quality Samsung LEDs is ideal for ambient lighting. Can also be recess or surface mounted using aluminium profiles, available to order separately. Can be shortened every 50 mm.




Aluminium profiles are available to order separately, shown from page 5.184



## Loox5 24V LED 3042 flexible strip light, 8 mm width






- Cut LED strip light to length (one contact side remains on the remainder piece; reusable)
- Connect LED strip lights (two contact sides required)

C = section length = 50 mm

P = length of contact surface = 4.0 mm

- > Equipped with high quality Samsung LEDs
- > For surface mounting, self adhesive, 5 m length
- > Can be shortened every 50 mm
- > Voltage: 24V. Wattage: 24W (4.8W per metre)
- > Dimmable
- > Degree of protection: IP20 > Lifetime: >50,000 h
- > Width: 8 mm
- > Height: 1.3 mm
- > Lead not included, must be ordered separately
- > White plastic
- > Order qty: 1 pc (roll of 5 m length)

Distance	120	2700 K	3000 K	4000 K	5000 K		
250 mm		1050 Lx	1090 Lx	1120 Lx	1130 Lx		
500 mm		435 Lx	455 Lx	460 Lx	470 Lx		
750 mm		240 Lx	245 Lx	260 Lx	260 Lx		
1000 mm		145 Lx	150 Lx	155 Lx	160 Lx		
The values apply to a strip light length of 1 m							





TCH DESIGN 2020, @ Häfele U.K. Ltd 2020. Dimensional data not binding. We reserve the right to alter specifications without notice.

- > Maximum strip length is dependant on driver wattage capacity, shown on page 5.157
- > Maximum recommended strip light length for optimum visual light output: 12.0 m
- > Lead must be ordered separately, shown on page **5.171**

Output:	2700 K	3000 K	4000 K	5000 K		
Light colour:	Warm white		Cool v	vhite		
Wattage (W):	4.8W per metre					
Energy efficiency:	A+	A+	A+	A+		
Number of diodes:	120 per metre					
Light output (Lm/m):	440	465	490	495		
Efficacy (Lm/W):	92	97	102	103		
CRI Ra / R9:	>90 / >50					













Length 3000 K 4000 K 2700 K 833.76.316 833.76.318 833.76.319 5 m 833.76.317

YOU ALSO NEED:







**OPTIONAL ACCESSORIES** Pages 5.158-159, 5.167-168, 5.178-181