

LOOX5 24V LED 3081 DOWNLIGHT

Create decorative effects with the LED 3081 RGB downlight by mixing any combination of light colours. The lights are controlled using the Häfele Connect Mesh system which must be ordered separately.



5


Lighting: Loox5 LED

Loox5 24V LED 3081 downlight, 65 mm



- > For surface mounting
- > Screw fixing
- > Voltage: 12V. Wattage: 0.7W
- > Colour control only via Häfele Connect Mesh 6-way distributor with RGB adapter, must be ordered separately
- > Degree of protection: IP20
- > With 2.0 m lead with Loox5 24V connector
- > Plastic housing
- > Order qty: 1 pc

EXTRA
FLAT
6 mm



Light colour:	RGB
Number of diodes:	6
Luminous flux (Lm):	20
Wattage (W):	0.7
Luminous efficacy (Lm/W):	29

TCH DESIGN 2020. © Häfele U.K. Ltd 2020. Dimensional data not binding. We reserve the right to alter specifications without notice.



Control using Häfele Connect Mesh system, shown from page 5.178

5 24V	RGB Colour	IP20	III	F	7 YEARS	Fixings included
Finish	RGB					
Silver coloured	833.77.230					

YOU ALSO NEED:

- DRIVER**
Page 5.157
- SWITCH**
Page 5.160-166
- CONTROL**
Page 5.178-180
- OPTIONAL ACCESSORIES**
Pages 5.159, 5.167-168