
LOOX5 12V/24V DISTRIBUTORS

The connection of the distributors with the driver can be done using a box to box plug-in connection or an extension lead. Any number of distributors can be connected to the driver but maximum wattage must be strictly observed.

Loox5 12V/24 Box to box 6-way distributor with switching function



- > With switching function; one switch controls all output ports
- > Dimensions (L x W x H): 120 x 50 x 16 mm
- > Number of connections:
 - 1x input port with box to box plug
 - 1x output port with box to box socket
 - 1x input port switch socket
 - 6x output ports device sockets
- > Black plastic
- > Order qty: 1 pc













Ensure maximum connected wattage is not exceeded



Loox5 12V/24 Box to box 6-way distributor without switching function



- > Without switching function
- > Dimensions (L x W x H): 130 x 50 x 16 mm
- > Number of connections:
 - 1x input port with box to box plug
 - 1x output port with box to box socket
 - 6x output ports device sockets
- > Black plastic
- > Order qty: 1 pc












Ensure maximum connected wattage is not exceeded

Voltage Max. connected wattage Cat. No. 12V 833.95.747 60W 90W 24V 833.77.832


Loox5 12V/24 6-way distributor without switching function



Can also be connected to box to box 6-way distributor



- > Without switching function, can also be connected to box to box 6way distributor
- > Dimensions (L x W x H): 70 x 30 x 14 mm
- > Number of connections:
 - 1x input port with box to box plug
 - 1x output port with box to box socket
 - 6x output ports device sockets
- > Black plastic
- > Order qty: 1 pc









ICH DESIGN 2020, © Häfele U.K. Ltd 2020. Dir



Ensure maximum connected wattage is not exceeded







A 6-way distributor for use with the Häfele Connect Mesh system is shown on page 5.178

19.02.20/1