

LOOX5 12V/24 LEADS - SILICONE, MONOCHROME, 8 MM

Loox driver to light connecting leads and light to light interconnecting leads and end cap, for Loox5 silicone flexible strip light LED 2063 shown on page 5.100. Use of these leads and end caps provides IP44 degree of protection.

Loox5 IP44 12V/24 driver to light lead, LED silicone strip light monochromatic, 8 mm



12V version



24V version

- > Current carrying capacity: Max 5 A
- > Width: Silicone plug 15 mm
- > Supplied with: 1x lead plug/clip
- > For drill hole Ø 8 mm plug
- > Plastic
- > Order qty: 1 pc

5 12V **5** 24V



Length	2000 mm
12V	833.95.703
24V	833.95.709

IP44 interconnecting lead, LED silicone strip light monochromatic, 8 mm




- > Current carrying capacity: Max 5 A
- > Clip width: 15 mm
- > Supplied with: 1x lead clip/clip
- > For drill hole Ø 15 mm clamp
- > Plastic
- > Order qty: 1 pc



Length	50 mm	500 mm	2000 mm
Cat. No.	833.89.203	833.89.204	833.89.205

LED 2063 end cap for IP44 degree of protection






- > End cap set with adhesive
- > For 8 mm LED silicone strip light LED 2063
- > For sealing the shortened silicone strip light
- > Set includes: 5 end caps, 1x 5 ml adhesive
- > Plastic
- > Order qty: 1 set



	Cat. No.
Set of 5, with 5 ml adhesive	833.89.184

IP20



If required an IP20 version of LED 2063 silicone strip lights can be created by using the leads and clips which are normally used for 8 mm monochrome flexible strip lights: IP20 leads and clips are shown on page 5.171

Häfele silicone stripper for LED silicone strip lights



- > For stripping silicone from Loox5 LED strip lights 2063 and 3046
- > Strip silicone strip light to max. 5 mm in order to use interconnecting leads or clip connectors
- > Strip more than 5 mm for IP20 clip connector
- > Can also be used to cut a cable completely
- > Grey and red plastic
- > Order qty: 1 pc

	Cat. No.
Silicone stripper for LED strip lights	006.13.485