


LOOX5 12V/24 EXTENSION LEADS

Extension leads for where longer cable lengths are needed from driver to device. Please note the maximum lead length from Loox5 driver to light is 10 m.

Loox5 12V/24 extension lead, monochromatic




- > For monochrome lights and other 2-core consumers and distributors
- > Current carrying capacity: Max 5 A
- > Supplied with: 1x extension lead, 1x plug/1 socket
- > Plastic
- > Order qty: 1 pc

5 12V 5 24V



Voltage	500 mm	1000 mm	2000 mm
12V	833.95.712	833.95.713	833.95.714
24V	833.95.719	833.95.718	833.95.717

Loox5 12V/24 extension lead, multi-white




- > For multi-white lights
- > Current carrying capacity: Max 3.5 A
- > Supplied with: 1x extension lead, 1x plug/1 socket
- > Plastic
- > Order qty: 1 pc

5 12V 5 24V



Voltage	12V	24V
2000 mm	833.95.715	833.95.720

Loox5 12V/24 extension lead, RGB




- > For RGB lights
- > Current carrying capacity: Max 3.5 A
- > Supplied with: 1x extension lead, 1x plug/1 socket
- > Plastic
- > Order qty: 1 pc

5 12V 5 24V



Voltage	12V	24V
2000 mm	833.95.716	833.95.721

Loox5 12V/24 4-way extension lead, monochromatic



- > For monochrome lights and other 2-core consumers and distributors
- > Current carrying capacity: Max 5 A
- > Supplied with: 1x extension lead, 1x plug/4 sockets
- > Plastic
- > Order qty: 1 pc

5 12V 5 24V



Voltage	12V	24V
6500 mm	833.95.742	833.95.743



Maximum lead length from the Loox5 driver to the device is 10 m. Long cable lengths in combination with large loads (strip light lengths) can result in voltage losses in the cable. These lead to visible loss of brightness in the lights. The illuminance listed with the lights has been determined with the rated output voltage of the driver (12 V or 24 V).

5

Lighting: Loox5 LED

TCH DESIGN 2020, © Hafele U.K. Ltd 2020. Dimensional data not binding. We reserve the right to alter specifications without notice.