LOOX ALUMINIUM PROFILES FOR RECESS MOUNTING

Loox profiles 1103, 1104 and 1105 include a white opal diffuser which creates a uniform light. The LED points are invisible from 120 LEDs/m. Profile 1105 also includes an anti-glare shield. Order alternative diffusers in black opal or transparent separately.



Loox 1104 aluminium profile, 11.5 mm depth, for Loox LED flexible strip lights, recess mounting

















Profile 1104 is only suitable for LED flexible strip lights with max. 5 mm width

- > Order profile and end caps separately
- > For recess mounting
- > With white opal plastic diffuser, 70-80% transmittance
- > Diffuser width: 8 mm
- > End caps with cable outlet
- > Anodised aluminium profile
- > Order aty:

Profile: 1 pc

End caps: 1 set - includes 10 pcs (5 pairs)



Colour	Black	Silver coloured		
Length 3000 mm	833.95.725	833.95.724		
Please order end caps separately:				
End caps (1 set = 10 pcs)	833.95.769	833.95.768		

Loox 1103 aluminium profile, 11.5 mm depth, for Loox LED flexible strip lights, recess mounting















- > Order profile and end caps separately
- > For recess mounting
- > With white opal plastic diffuser
- > Diffuser width: 11 mm
- > End caps with cable outlet
- > Anodised aluminium profile
- > Order qty:

Profile: 1 pc

End caps: 1 set - includes 10 pcs (5 pairs)



Colour	Black	Silver coloured	
Length 3000 mm	833.95.723	833.95.722	
Please order end caps separately:			
End caps (1 set = 10 pcs)	833.95.767	833.95.766	



End caps

The diffuser creates a uniform light. The LED points are invisible from 120 LEDs/m. If required, please order alternative diffusers in black opal or transparent separately. Please see page 5.185