

Product	Clam Peel Coat
Type	Wax-based water-borne release coat.
Intended Use	For application onto most walls including plaster, plywood, hardboard etc. prior to hanging of wallcoverings using normal adhesive systems in order to facilitate the subsequent easy removal of said wallcoverings during redecoration without the need for soaking, steaming and scraping.
Special Features	Non-flammable. Low VOC content. Has pale green tint to indicate where Peel has been applied. User friendly. Gives high shear strength bonding of wallcoverings, but relatively low peel strength for easy removal. Enables quick redecoration with significant savings in time & labour costs. May be painted over if such a finish is required in the future.
Preparation	Walls and surfaces must be clean, dry and free from loose paint, plaster or dust. New plaster must be completely dry.
Application	Dilute one part of Peel with approximately 1/3 parts of water and stir thoroughly prior to use. Apply evenly with a brush or roller, making sure it is well brushed out.
Coats	One coat. Do not apply to previously coated areas.
Drying Time	Leave Peel for one hour before hanging.
Re-coating Time	Not applicable. One coat will last 3 – 4 decorations before reapplication is necessary.
Application Temp.	Ideally between 15 – 25 Degrees C.
Coverage	Approximately 25 sq. metres per litre when diluted as instructed. One coat will last 3 – 4 decorations before reapplication is necessary.
Maintenance	Not applicable.
Compatibility	Can be used on most substrates including plaster, plywood, hardboard etc. Using Peel ensures all surfaces are perfectly sealed and primed. As the wall covering comes off in complete sheets it may be re-used elsewhere.
Settlement	Not applicable
Shelf-life/Storage	Minimum 12 months when stored in a cool, dry place out of direct sunlight in the original, sealed container. Do not store below +5 degrees Centigrade.
Hazards	Irritant. Avoid eye and skin contact. In case of skin or eye contact wash copiously with water. Wear suitable protective glasses and gloves. Keep away from children. Health and Safety Data Sheet available on request or from website.
Clean-Up	Clean equipment with warm soapy water.
Sizes	5 lt. (BM75) plastic containers.