



Beeswax Paste

- Traditional wax that nourishes wood
- Feeds wood and protects against dryness
- Gives an authentic finish
- Ideal for small surfaces and furniture
- Suitable for hard and softwoods
- EN71 Part 3 Approved – Safe for toys
- Approved by the Guild of Master Craftsmen

USAGE

Interior

COVERAGE

1 Litre

10-12 m²

APPLICATION

Cloth or
brush

DRYING TIME

Minimum
1 hour

TOOL CLEANING

Turpentine

Product use

Liberon Beeswax Paste is ideal for nourishing absorbent woods such as pine and oak, especially unsealed. It naturally protects wood and guards against dryness. It is particularly suitable for small surfaces and furniture.

Preparation

Remove old waxes and dirt with Liberon Wax and Polish Remover if necessary. Ensure the surface is clean, dry and free from dust.

Application

Apply a coat of Liberon Beeswax Paste sparingly with a soft, lint-free cotton cloth or Liberon Ultra Fine Steel Wool (0000). Allow to dry for a minimum of 1 hour – longer if possible, then buff with a clean cotton cloth or Liberon Drill Brush. Repeat the operation on new or very dry wood as it may require two or more coats.

For a higher sheen build-up with thin coats of Beeswax, buffing between coats. Buff with a Liberon Furniture Brush or Drill Brush once the last coat has completely dried.

Important: Always test product on a spare surface or inconspicuous area for colour, compatibility and end result.

Cleaning and maintenance

Wipe over with a cloth or duster and re-wax as required when the surface looks dull and tired. Do not wash with water.

Precautions

- Not suitable for high water areas such as kitchens and bathrooms.

Colours: Clear, Dark and Antique Pine.

Packaging

150 ml, 500 ml, 5 L

For further information on this or other Liberon products please contact Liberon Technical Services on 01797 361136.

This document was created with Win2PDF available at <http://www.daneprairie.com>.
The unregistered version of Win2PDF is for evaluation or non-commercial use only.